



## TECHNICAL DATA SHEET

# KEIM ROMANIT®-SCHLÄMMZUSATZ

## 1. PRODUCT DESCRIPTION

---

KEIM Romanit-Schlämmzusatz is a powdery mineral slurry additive for lime paint formulations in the KEIM Romanit system. KEIM Romanit-Schlämmzusatz Contains valuable silicates of various grain shapes in a well-balanced composition.

## 2. FIELD OF APPLICATION

---

KEIM Romanit-Schlämmzusatz is added to the KEIM Romanit system for slurry and/or structure-adjusting coatings.

## 3. PRODUCT PROPERTIES

---

- mineral
- structure-equalising
- high filling capacity

### COLOUR SHADES:

Light grey

## 4. APPLICATION INSTRUCTIONS

---

### SUBSTRATE PREPARATION:

The substrate must be dry, sound, free from chalking, clean and dust-free. Loose parts of existing coatings must be removed mechanically or by high-pressure water jetting. Defective areas must be filled and texture-matched using a suitable repair material. Any sintered layers on new renders must be removed with KEIM Fluat-10 according to instructions. New render areas (repairs) are generally to be pretreated with KEIM Fluat-10 according to the specifications in the Technical Data Sheet.

### APPLICATION CONDITIONS:

Ambient and substrate temperature  $\geq 10$  °C during application and drying. Do not apply in direct sunlight or on sun-heated substrates. Protect surfaces from direct sun, wind and rain during and after application.

### CONSUMPTION:

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

### APPLICATION:

The admixture of KEIM Romanit-Schlämmzusatz is determined by the lime-experienced applicator. This decision is derived from the object-related conditions and historical experience.

### CLEANING OF TOOLS:

Clean immediately with water.

## TECHNICAL DATA SHEET – KEIM ROMANIT®-SCHLÄMMZUSATZ

### 5. PACKAGING

Container content	Unit of measure	Quantity on pallet
5	kg	70
20	kg	24

### 6. STORAGE

max. storage time	Storage conditions
unlimited storage time	keep container tightly sealed. dry

### 7. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

Waste code: 08 01 12

### 8. SAFETY INSTRUCTIONS

Please, refer to the Material Safety Data Sheet. EU limit value for this product .  
This product contains: - g/L VOC.

### 9. GENERAL INFORMATION

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.  
Mixing with products not part of the system or other foreign additives is not permitted.

### 10. CERTIFICATES & QUALITY SEALS



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.